

DECLARATION OF PERFORMANCE	
Reference :	DOPClicwallv1
Commercial name :	Clicwall
Product type :	Melamine faced MDF Fibreboard
Reference standard :	Wood Based Panel - EN 13986 Annex A Table A.9
CE Class :	MDF
Field of application :	Walls (Internal use as non-structural component in dry conditions - Service Class 1)
AVCP Class :	1
Produced at:	Breestraat 4,B-8710 Wielsbeke
	Ingelmunstersteenweg 299,B-8780 Oostrozebeke
	Ooigemstraat 3, B-8710 Wielsbeke

Essential Characteristic	Unit	Reference		
			10mm	12mm
Bending strength	N/mm ²	EN 622-5 - table 3	22	22
Bending stiffness	N/mm ²	EN 622-5 - table 3	2500	2500
Internal bond	N/mm ²	EN 622-5 - table 3	0,60	0,60
Formaldehyde emission class	Class	EN 13986-table B1	E1	E1
Formaldehyde content	mg/100g	EN 120	≤ 8	≤ 8
Reaction to fire	Class	EN 13501-1	D-s2,d0	B-s1,d0
Water vapour permeability μ	wet	EN 13986-table 9	NPD	NPD
	dry		NPD	NPD
Airborne sound insulation	dB	EN 13986-5.10	NPD	NPD
Sound absorption α		EN 13986-table 10	0,10/0,20	0,10/0,20
Thermal conductivity λ	W/m.K	EN 13986-table 11	0,13	0,13
Biological durability	Service Class	EN 335	1	1
Content of PCP	ppm	EN 13986-5.18	<5	<5

Version date :
14/09/2018

Lode De Boe,
President UNILIN bvba, division panels

