

DECLARATION OF PERFORMANCE	
Reference :	DOPClicwallFRv2
Commercial name :	Clicwall FR
Product type :	Fire retardant melamine faced MDF Fibreboard
Reference standard :	Wood Based Panel - EN 13986 Annex A Table A.9
CE Class :	MDF
Field of application :	Walls
AVCP Class :	1
Certification number:	1161-CPR-1275 (10mm)
Produced at:	Breestraat 4,B-8710 Wielsbeke
	Ingelmunstersteenweg 299,B-8780 Oostrozebeke
	Ambachtenstraat 68, B-8870 Izegem

Essential Characteristic	Unit	Reference	10mm
Bending strength	N/mm ²	EN 622-5 - table 3	22
Bending stiffness	N/mm ²	EN 622-5 - table 3	2500
Internal bond	N/mm ²	EN 622-5 - table 3	0,60
Formaldehyde emission class	Class	EN 13986-table B1	E1
Formaldehyde content	mg/100g	EN 120	≤ 8
Reaction to fire	Class	EN 13501-1	B-s2,d0
Water vapour permeability μ	wet	EN 13986-table 9	NPD
	dry		NPD
Airborne sound insulation	dB	EN 13986-5.10	NPD
Sound absorption α		EN 13986-table 10	0,10/0,20
Thermal conductivity λ	W/m.K	EN 13986-table 11	0,13
Biological durability	Service Class	EN 335	1
Content of PCP	ppm	EN 13986-5.18	<5

Version date :
22/01/2016

Lode De Boe,
President UNILIN bvba, division panels

